



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666



Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier CHROMIUM REFERENCE SOLUTION 1000PPM		Product Use Laboratory use	
Chemical formula Cr / HCl		Product code AA-0900	Molar weight 52
Chemical name / Commercial name / Synonymous Étalon Chrome 1000ppm			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666		CENTRE ANTI-POISON DU QUÉBEC 800-463-5060
Date SDS 10/30/2020	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Corrosive to metals-Category 1 Serious eye damage/eye irritation - Serious eye damage category 1 Skin corrosion/irritation - Skin corrosion category 1
Signal Word	DANGER
Hazards statements (H)	H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.
Precautionary statements (P)	P264 Wash the areas of the body that have been in contact with the product after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection. P321 Specific treatment (see section 4 of the SDS and on this label). P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P234 Keep only in original container. P260 Do not breathe dust / fume / gas / mist / vapors / spray. P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P310 Immediately call a POISON CENTER or doctor/physician. P363 Wash contaminated clothing before reuse. P390 Absorb spillage to prevent material damage. P405 Store locked up. P406 Store in a corrosion resistant container / or a container with corrosion resistant liner. P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.
PICTOGRAMS	
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	Health 2 Fire 0 Reactivity 0 Special danger

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Chrome	7440-47-3	0.1
Acide chlorhydrique	7647-01-0	4

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	The product is a material corrosive. Main symptoms of high exposure: Eyes irritation. Skin irritation. Irritation of the respiratory system. Pneumonia. Pulmonary edema. Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	Not flammable or combustible.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Not applicable.
Hazardous combustion products	Hazardous combustion products formed under fire conditions: - Hydrogen chloride gas
Special fire and explosion hazards	May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personal precautions, protective equipment	Evacuate personnel to safe areas. Absorb the product with sand or vermiculite. Dilute residues with water, clean and rinse. Ensure a good ventilation of the premises. Dispose of residues in a container for disposal of hazardous materials. When handling, wear suitable safety equipment. Use breathing apparatus if necessary. Avoid breathing vapors, mist or gas.
---	--

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Keep container tightly closed and store away from incompatible products, heat, sparks, and open flame. Store away from heat and light. Do not store in metal containers.
Methods of handling	Avoid inhalation of vapor or mist. Avoid ingestion and inhalation. Avoid contact with the skin, eyes and clothes. This product is corrosive to metals. Do not use metal instruments to handle this product. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Hydrochloric acid	7647-01-0	(c)	2.000000 ppm 3.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		C	2.000000 ppm	Canada. British Columbia OEL
		C	5.000000 ppm 7.500000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	A substance which may not be recirculated in accordance with section 108			
		(c)	2 ppm 3 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		C	2 ppm	Canada. British Columbia OEL
		C	5 ppm 7.5 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	A substance which may not be recirculated in accordance with section 108			
		C	2.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		C	2 ppm	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Use fan.
Respiratory	If work under the hood is not possible, or if the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Liquide bleu.
Odour	Inodore.
Odour threshold	Data not available
pH	<1.
Melting point / Freezing point	Data not available
Initial boiling point	103°C
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Solubility	Miscible avec l'eau en toutes proportions.
Vapour density	Data not available
Relative density	1.008g/ml
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Acid product, reacts strongly with strong bases. Reacts strongly with metals.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	May react violently with incompatible substances.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Avoid contact with incompatible materials and extreme temperatures.
Incompatible material	When pure, the products react with the following products: Bases, Amines, alkali metals, metals, permanganates, fluorine, metal acetylides, hexalithium disilicide. Strong acids, strong oxidants. Carbon dioxide (CO ₂).
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. Toxic fumes of chromium oxides. - Hydrogen chloride gas

SECTION 11 - TOXICOLOGICAL INFORMATION

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and tearing.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Nervous disorders, chest pain, cough, dyspnea, headache, dizziness, confusion, nausea and vomiting.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Abdominal pain, liver and kidney damage, cramps, diarrhea, headache, dizziness, sweating, salivation, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, nervous disorders, lung damage (pulmonary fibrosis and pneumoconiosis), chest pain, cough, dyspnea, laryngitis, headache, dizziness, confusion, irritability, sweating, salivation, metallic taste in the mouth, fatigue, fever, nausea and vomiting. Is recognized as an unclassifiable agent for its carcinogenicity (Group 3 according to IARC).
DL50 (specify species and route of entry)	LD50 Oral - Rat - 5,000 mg/kg. LD50 Dermal: Data not available.
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 5.41mg/L.

HYDROCHLORIC ACID

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe burns and destruction of ocular tissue that can lead to corneal ulceration and blindness.
- Skin	Severe burns and tissue ulcerations. Perhaps fatal, if the extent of the burns is considerable.
- Inhalation	Spasms, irritation and inflammation of the nose, throat and lungs. Edema of the larynx and bronchi. Chemical pneumonitis and pulmonary edema that can lead to death.
Acute toxicity (Ingestion)	Corrosion and ulceration of the mouth, throat, esophagus, stomach and abdominal wall. Dysphagia, abdominal pain, cramps, diarrhea, melena, hematemesis, possible perforation of the esophagus and stomach, sweating, salivation.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, conjunctivitis, photophobia, lung and eye damage, chest pain, dental enamel abrasion, cough, dyspnoea, laryngitis, tracheobronchitis, headache, dizziness, fever, sweating, salivation, thirst.
DL50 (specify species and route of entry)	Oral 238-277 mg/Kg-Rat LD50 - Dermal 1449 mg/kg-Mouse
CL50 (specify species and route of entry)	LC50 - Inhalation - 3124 ppm/1 h.-Rat

SUMMARY

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	May cause irritation of the digestive tract.
Inhalation	Causes burns. Effects may be delayed.
Skin	May cause irritation or burns of the skin.
Eyes	May cause irritation or burns of the eyes.
Chronic exposure effects / Symptoms:	May cause irritation or burns. To our knowledge, the product has not been fully evaluated
ETA Mix (Estimated Acute Toxicity)	LD50: >5000 mg/kg -Oral Rat LD50: >5000 mg/kg Dermal Mouse LC50: 58mg/L - 4 hres- Inhalation Rat

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Hydrochloric acid: Toxicity to fish LC50 - Lepomis macrochirus (Bluegill) - 24.6 mg/l - 96 h (Hydrochloric acid) Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna (Water flea) - 4.91 mg/l - 48 h (Hydrochloric acid)
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Data not available.
Other adverse effects	Avoid release to the environment.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	3264
UN Proper shipping name	LIQUIDE CORROSIF, ACIDE, INORGANIQUE, N.S.A. (acide chlorhydrique)
Transport hazard class(es)	8 Corrosive substances
Packing group	III
Limited quantity index	5L
ERAP Index	-
Special precautions	16

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Corrosive to metals-Category 1 Serious eye damage/eye irritation - Serious eye damage category 1 Skin corrosion/irritation - Skin corrosion category 1
--------------	--

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 10/30/2020