



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666



Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier BUTYL ACETATE		Product Use Laboratory use	
Chemical formula CH ₃ CO ₂ (CH ₂) ₃ CH ₃		Product code BR-0153	Molar weight 116,16
Chemical name / Commercial name / Synonymous ACÉTATE DE BUTYLE NORMAL, BUTYL ACETATE, n-BUTYL ACETATE, ACETIC ACID BUTYL ESTER, BUTYL ETHANOATE, 1-BUTYL ACETATE			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666		CENTRE ANTI-POISON DU QUÉBEC 800-463-5060
Date SDS 4/17/2020	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	<p>Flammable liquids category 3</p> <p>Specific target organ toxicity - Single exposure category 3</p> <p>Skin corrosion/irritation - Skin irritation category 2</p> <p>Serious eye damage/eye irritation - Eye irritation category 2</p>
Signal Word	<p>WARNING</p>
Hazards statements (H)	<p>H226 Flammable liquid and vapour.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p>
Precautionary statements (P)	<p>P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical/ventilating/lighting equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P261 Avoid breathing dust / fume / gas / mist / vapours / spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</p> <p>P312 Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>P403 + P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403 + P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.</p> <p>P370 + P378 In case of fire: Use water spray or alcohol-resistant foam, or dry powder or carbon dioxide for extinction.</p> <p>P264 Wash the areas of the body that have been in contact with the product after handling.</p> <p>P321 Specific treatment (see section 4 of the SDS and on this label).</p> <p>P302 + P352 IF ON SKIN: Wash with plenty of soap and water.</p> <p>P332 + P313 If skin irritation occurs: Get medical advice/attention.</p> <p>P362 + P364 Take off contaminated clothing and wash it before reuse.</p> <p>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337 + P313 If eye irritation persists: Get medical advice/attention.</p>
PICTOGRAMS	
Other dangers	<p>NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)</p>
	<p>Health 1</p> <p>Fire 3</p> <p>Reactivity 0</p> <p>Special danger</p>

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Acétate de butyle	123-86-4	<=100

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	If breathed in, move person into fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	Yes
Ignition conditions	Strong oxidizing agents, heat, sparks and open flame. Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.
Suitable extinguishing media	Water spray, carbon dioxide, dry chemical powder, alcohol or polymer foam.
Unsuitable extinguishing media	Do not use a heavy water stream.
Hazardous combustion / decomposition products	Hazardous decomposition products formed under fire conditions. Carbon oxides.
Special fire and explosion hazards	Steam can travel a great distance and ignite on sources of ignition such as heaters, electrical appliances, cigarettes, sparks, etc. Closed containers exposed to fire can explode. Vapors may form flammable or explosive mixtures with air. May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personnel precautions, protective equipment	Evacuate personnel to safe areas. Cut off all sources of ignition. Absorb the product with sand or vermiculite. Dilute residues with water, clean and rinse. Ensure a good ventilation of the premises. Dispose of residues in a container for disposal of hazardous materials. When handling, wear suitable safety equipment. Use breathing apparatus if necessary. Avoid breathing vapours, mist or gas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not let product enter drains.
--	---

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in a cool, dry place. Use venting and electrical equipment that is grounded and does not produce ignition sources (sparks). Protect from the sun's rays. Keep container tightly closed in a dry and well-ventilated place. Keep container tightly closed and store away from strong oxidants, heat, sparks and open flame.
Methods of handling	Bottle in the glass only. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
n-Butyl acetate	123-86-4	TWA	20.000000 ppm	Canada. British Columbia OEL
		STEL	200.000000 ppm 950.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWA	150.000000 ppm 713.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWAEV	150.000000 ppm 710.000000 mg/m3	Canada. Ontario OELs
		STEV	200.000000 ppm	Canada. Ontario OELs
			950.000000 mg/m3	
		TWAEV	150.000000 ppm 713.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	150 ppm 713 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	200.000000 ppm 950.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	200 ppm 950 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	150 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	150.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Fan.
Respiratory	If work under the hood is not possible, or if the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Liquide incolore .Odeur fuitée caractéristique-
Odour	Donnée non disponible.
Odour threshold	7.0ppm
pH	6.2 à 5.3 g/L à 20 °C.
Melting point / Freezing point	-78°C
Initial boiling point	126°C
Boiling range	124 -126°C
Flash point	22°C
Evaporation rate	1.0.
Flammability	Yes
Lower flammable / Explosive limit	1.7%
Upper flammable / Explosive limit	7.6%
Vapour pressure	8.0 mm @ 20°CmmHg
Vapour density	4.0 (Air=1)-
Relative density	0.882g/ml
Solubility	Peu soluble dans l'eau (5.3 g/L à 20 °C). Miscible avec l'alcool, l'éther et le propylène glycol.
Partition coefficient water/n-octanol	0.015-
Auto-ignition temperature	415°C
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Highly flammable liquid and vapours. Vapours may form explosive mixture with air. May react violently with incompatible substances.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Heat, flames and sparks. Avoid the accumulation of static electricity.
Incompatible material	Strong oxidizing agents (nitric acid, perchloric acid, peroxides, chlorates and perchlorates), strong reducing agents (potassium, sodium, metal hydrides), strong acids and bases, alkalis, nitrates, potassium tert-butoxide, heat and humidity.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. Toxic vapors of carbon monoxide and dioxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

BUTYL ACETATE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe irritation and may result in inflammation of the conjunctiva.
- Skin	Irritation and dermatitis.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Narcotic effects, chest pain, cough, dyspnea, headache, rhinitis, dizziness, drowsiness, nausea and vomiting, convulsions and may cause loss of consciousness.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Gastrointestinal disorders, cramps, diarrhea, headache, dizziness, drowsiness, tremors, convulsions, salivation, nausea and vomiting.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, conjunctivitis, narcotic effects, lung and eye damage, chest pain, cough, dyspnea, headache, dizziness, listlessness, drowsiness, confusion, irritability, muscle weakness, weight loss and weight loss appetite, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - female - 10760 mg/kg LD50 Dermal - Rabbit - 14112mg/kg.
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 1087- 9312 ppm. 740 - 71 500 mg/m ³

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Toxicity to fish: Flow-through test - LC50 - Pimephales promelas (fathead minnow) - 18 mg/L - 96 h. Toxicity to daphnia and other aquatic invertebrates: Static test: EC50 - Daphnia magna (Water flea) - 44 mg/L - 48h. Toxicity to algae: Static test: CE50r - Pseudokirchneriella subcapitata (algues vertes) - static test - 397 mg/l - 72 h Toxicity to bacteria: Static test: IC50 - Tetrahymena pyriformis - 356 mg/l - 40 h.
Persistence and degradability	Biodegradability aerobic. Method: OECD Test Guideline 301D. Result: 83 % - Readily biodegradable
Bioaccumulative potential	Data not available.
Mobility in soil	Data not available.
Other adverse effects	Harmful to aquatic life. All littering must be avoided in the environment. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	1123
UN Proper shipping name	ACÉTATES DE BUTYLE
Transport hazard class(es)	3 Flammable liquids
Packing group	III
Limited quantity index	5L
ERAP Index	-
Special precautions	-

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Flammable liquids category 3 Specific target organ toxicity - Single exposure category 3 Skin corrosion/irritation - Skin irritation category 2 Serious eye damage/eye irritation - Eye irritation category 2
---------------------	--

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 4/17/2020