



Centre Anti-Poison pour le Québec: (800) 463-5060  
 Tél. (Qc): (418) 660-8666 / 800-890-8666  
 Fax. (Qc): (418) 660-8998

## SAFETY DATA SHEET

### SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier CALCIUM (GRANULES)		Product Use Laboratory use	
Chemical formula Ca		Product code CR-0109	Molar weight 40,08
Chemical name / Commercial name / Synonymous CALCIUM METAL, CRYSTALLINE, CALCICAT			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666	CENTRE ANTI-POISON DU QUÉBEC 800-463-5060	
Date SDS 7/29/2020	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

### SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Substances and mixtures which, in contact with water, emit flammable gases category 2
Signal Word	DANGER
Hazards statements (H)	H261 In contact with water releases flammable gases.
Precautionary statements (P)	<p>P223 Keep away from any possible contact with water, because of violent reaction and possible flash fire.</p> <p>P231 + P232 Handle under inert gas. Protect from moisture.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P370 + P378 In case of fire: Use special powder for metal fires; do not use water for extinction.</p> <p>P402 + P404 Store in a dry place. Store in a closed container.</p> <p>P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.</p>
PICTOGRAMS	
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	<p>Health 2</p> <p>Fire 3</p> <p>Reactivity 2</p> <p>Special danger EAU</p>

### SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Calcium	7440-70-2	<=100

## SECTION 04 - FIRST AID MEASURES

<b>Eye contact</b>	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
<b>Skin contact</b>	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
<b>Inhalation</b>	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
<b>Ingestion</b>	If the person is conscious, rinse the mouth with water. Never give anything by mouth to an unconscious person. Consult a physician.
<b>Most important symptoms and effects (acute and delayed)</b>	Ref. section 11.
<b>Immediate medical attention and special treatment, if necessary</b>	In case of medical consultation, keep this sheet available.
<b>General advice</b>	Show this safety data sheet to the doctor in attendance.

## SECTION 05 - FIREFIGHTING MEASURES

<b>Flammability</b>	Yes
<b>Ignition conditions</b>	Heat, sparks and open flame. Sensitive to air.
<b>Suitable extinguishing media</b>	Use a Class D fire extinguisher or special powder for metal fires. Dry powder.
<b>Unsuitable extinguishing media</b>	Do not use water.
<b>Hazardous combustion / decomposition products</b>	Hazardous decomposition products formed under fire conditions. - Calcium oxide. Releases hydrogen (a flammable gas) on contact with water.
<b>Special fire and explosion hazards</b>	May react violently with incompatible products (Ref Section 10). This metal reacts strongly with water to release hydrogen, a flammable and explosive gas.
<b>Special protective equipment and precautions for firefighters</b>	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

## SECTION 06 - ACCIDENTAL RELEASE MEASURES

<b>Methods and materials for containment and cleaning up / Personal precautions, protective equipment</b>	Evacuate personnel to safe areas. Ensure adequate ventilation. Avoid breathing vapours, mist or gas. Use personal protective equipment. Pick up with a shovel or broom, taking care not to scatter dust. Avoid contact with water. Dispose of residues in a container provided for the disposal of hazardous materials. Do not let product enter drains.
---	--

## SECTION 07 - HANDLING AND STORAGE

<b>Conditions for safe storage</b>	Store in a cool, dry place. Keep container tightly closed and store away from heat, moisture, and incompatible products. Never allow product to get in contact with water during storage. Handle and store under inert gas. Air sensitive.
<b>Methods of handling</b>	Provide appropriate exhaust ventilation at places where dust or vapor is formed. Keep away from sources of ignition - No smoking. Keep away from moisture. Avoid contact with the skin, eyes and clothes. Avoid contact with water. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

## SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

### Workplace control parameters

Components	CAS-No.	Control	Value	Basis
Calcium (granule)	7440-70-2	TLV, TWA, STEL	No data available	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TLV, TWA, STEL	No data available	Canada. British Columbia OEL
		TLV, TWA, STEL	No data available	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

<b>Ventilation</b>	Fan.
<b>Respiratory</b>	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
<b>Gloves</b>	Handle with gloves.
<b>Eyes</b>	Safety goggles with safety shutters.
<b>Shoes</b>	Safety shoes.
<b>Clothing</b>	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
<b>Engineering control</b>	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

## SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Solid.
<b>Appearance</b>	granuleux argent-
<b>Odour</b>	inodore.
<b>Odour threshold</b>	Data not available
<b>pH</b>	14.
<b>Melting point / Freezing point</b>	845°C
<b>Initial boiling point</b>	1484 °C (2.703°F) - lit-
<b>Boiling range</b>	Data not available
<b>Flash point</b>	Data not available
<b>Evaporation rate</b>	Data not available
<b>Flammability</b>	Yes
<b>Lower flammable / Explosive limit</b>	Data not available
<b>Upper flammable / Explosive limit</b>	Data not available
<b>Vapour pressure</b>	10 mmHg @ 983°C-
<b>Vapour density</b>	Data not available
<b>Relative density</b>	1.54g/cm <sup>3</sup>
<b>Solubility</b>	Soluble dans l'ammoniaque liquide.
<b>Partition coefficient water/n-octanol</b>	Data not available
<b>Auto-ignition temperature</b>	Data not available
<b>Decomposition temperature</b>	Data not available
<b>Viscosity</b>	Data not available

## SECTION 10 - STABILITY AND REACTIVITY

<b>Reactivity</b>	Non-reactive under normal conditions.
<b>Chemical stability</b>	Stable under recommended storage conditions.
<b>Possibility of hazardous reactions</b>	Stable under normal conditions. Reacts violently with water.
<b>Conditions of instability (Including sensitivity to shock / static discharge / vibration)</b>	Reacts violently with water Sensitive to moisture and air.
<b>Incompatible material</b>	Strong oxidizing agents. Ammoniac. Water. Alcohols. Halogens. Oxygen.
<b>Hazardous decomposition products</b>	Hazardous decomposition products formed under fire conditions. - Calcium oxide. Releases hydrogen (a flammable gas) on contact with water.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### CALCIUM (GRANULES)

<b>Routes of exposure</b>	Ingestion, inhalation, skin and eyes.
<b>Acute exposition effects / symptoms:</b>	By exposure route below.
<b>- Eyes</b>	Irritation.
<b>- Skin</b>	Irritation and dermatitis.
<b>- Inhalation</b>	Extremely destructive to the tissues of the mucous membranes and the upper respiratory system. Spasms, inflammation and edema of the larynx and bronchi, chemical pneumonitis and pulmonary edema.
<b>Acute toxicity (Ingestion)</b>	May be harmful if swallowed.
<b>Chronic exposure effects / symptoms</b>	Burning sensation, cough, laryngitis, shortness of breath, headache, nausea and vomiting.
<b>DL50 (specify species and route of entry)</b>	LD50 Oral - Data not available. LD50 Dermal - Data not available.
<b>CL50 (specify species and route of entry)</b>	LC50 - Inhalation - Data not available.

## SECTION 12 - ECOLOGICAL INFORMATION

<b>Available ecological information</b>	No
---	----

## SECTION 13 - DISPOSAL CONSIDERATIONS

<b>Waste Disposal Method</b>	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
<b>Contaminated Packaging</b>	Dispose of as unused product.

## SECTION 14 - TRANSPORT INFORMATION

<b>UN Number</b>	1401
<b>UN Proper shipping name</b>	CALCIUM
<b>Transport hazard class(es)</b>	4.3 Substances which, on contact with water, emit
<b>Packing group</b>	II
<b>Limited quantity index</b>	0,5kg
<b>ERAP Index</b>	3000
<b>Special precautions</b>	-

## SECTION 15 - REGULATORY INFORMATION

<b>WHIMS CANADA</b>	Substances and mixtures which, in contact with water, emit flammable gases category 2
---------------------	---

## SECTION 16 - OTHER INFORMATION

### Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 7/29/2020