




Centre Anti-Poison pour le Québec: (800) 463-5060
 Tél. (Qc): (418) 660-8666 / 800-890-8666
 Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier SODIUM BISULFITE 12%W/V		Product Use Laboratory use	
Chemical formula NaHSO ₃		Product code SS-0712	Molar weight 104,06
Chemical name / Commercial name / Synonymous SODIUM BISULFITE, SODIUM HYDROGENSULFITE, SODIUM ACID SULFITE, SODIUM SULHYDRATE, SULFUROUS ACID MONOSODIUM SALT			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666	CENTRE ANTI-POISON DU QUÉBEC 800-463-5060	
Date SDS 9/14/2020	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Not a hazardous substance according to WHMIS 2015
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	Health 1 Fire 0 Reactivity 0 Special danger

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Bisulfite de sodium	7631-90-5	11
Eau	7732-18-5	Balance

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	Not flammable or combustible.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Data not available.
Hazardous combustion products	Hazardous combustion products formed under fire conditions: - Sulphur oxides, Sodium oxides.
Special fire and explosion hazards	Mixing sodium metabisulfite with sodium nitrite may result in a violent exothermic reaction. Contact with strong oxidizing agents and / or oxidizing materials may cause fire. Sodium metabisulfite combined with small amounts of water gives off heat. May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personal precautions, protective equipment	Evacuate personnel to safe areas. Absorb the product with sand or vermiculite. Dilute residues with water, clean and rinse. Ensure a good ventilation of the premises. Dispose of residues in a container for disposal of hazardous materials. When handling, wear suitable safety equipment. Use breathing apparatus if necessary. Avoid breathing vapours, mist or gas. Do not let product enter drains.
---	--

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in a cool, dry place. Do not store near acids. May break down if exposed to air for too long. Keep container tightly closed and store away from heat, moisture, and incompatible products. Air and moisture sensitive.
Methods of handling	Always open containers slowly to allow any excess pressure to vent. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust or vapor is formed. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Sodium hydrogensulphite	7631-90-5	TWA	5.000000 mg/m ³	Canada. British Columbia OEL
		TWAEV	5.000000 mg/m ³	Canada. Ontario OELs
		TWA	5.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWAEV	5.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	5 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	5.000000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
Not classifiable as a human carcinogen				
		TWA	5.000000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		TWA	5 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
Sodium metabisulphite	7681-57-4	TWA	5.000000 mg/m ³	Canada. British Columbia OEL
		TWAEV	5.000000 mg/m ³	Canada. Ontario OELs
		TWA	5.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required			
		TWAEV	5.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	5 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEL	5.000000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		TWA	5.000000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Liquide translucide jaunâtre-
Odour threshold	Data not available
Melting point / Freezing point	Data not available
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Vapour density	Data not available
Relative density	Data not available
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Stable under normal conditions.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Sensitive to moisture and air. If exposed to air, this product gradually oxidizes to sulphate, releasing corrosive vapors of sulphurous acid.
Incompatible material	When pure, the product reacts with the following products: Strong acids, strong oxidants. Strong oxidizing agents (nitric acid, perchloric acid, peroxides, chlorates and perchlorates), strong acids, aluminum, air and moisture.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. - Sulphur oxides, Sodium oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

SODIUM BISULFITE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe irritation and may result in inflammation of the conjunctiva.
- Skin	Irritation and dermatitis. May cause an allergic and inflammatory reaction of the skin as hives.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Nervous disorders, chest pain, respiratory allergy, cough, dyspnea, headache, dizziness, erythema, shortness of breath, nausea and vomiting. NOTE: High dust exposure can lead to seizures, respiratory failure and even cardiovascular collapse.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Gastrointestinal disorders, abdominal pain and cramps, diarrhea, headache, dizziness, sweating, salivation, seizures, nausea and vomiting.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, conjunctivitis, respiratory and skin allergies, nervous disorders, chest pain, cough, dyspnea, headache, dizziness, confusion, irritability, watery eyes, shortness of breath, erythema, tiredness, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 1540 mg/kg LD50 Dermal - Rabbit - 2000 mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 4h - 5.5 mg/L.

SUMMARY

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	To our knowledge, the product has not been fully evaluated
Inhalation	To our knowledge, the product has not been fully evaluated
Skin	To our knowledge, the product has not been fully evaluated
Eyes	To our knowledge, the product has not been fully evaluated
Chronic exposure effects / Symptoms:	To our knowledge, the product has not been fully evaluated
ETA Mix (Estimated Acute Toxicity)	LD50 Oral: > 5000 mg/kg - Rat LD50 Dermal: > 5000 mg/kg - Rabbit LC50 Inhalation: 51.3 mg/L - 4h - Rat

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Sodium bisulfite: Toxicity to fish: LC50: = 240 mg / L, 96h static (<i>Gambusia affinis</i>) Toxicity to daphnia and other aquatic invertebrates: EC50: = 119 mg/L, 48h (<i>Daphnia magna</i>)
Persistence and degradability	Soluble in water. Persistence is unlikely based on information provided.
Bioaccumulative potential	Data not available.
Mobility in soil	Probable mobility in the environment due to its solubility in water.
Other adverse effects	Harmful to aquatic life. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
-----------------------	--

SECTION 14 - TRANSPORT INFORMATION

UN Number	N/R
UN Proper shipping name	
Transport hazard class(es)	
Packing group	
Limited quantity index	
ERAP Index	
Special precautions	

SECTION 15 - REGULATORY INFORMATION

WHMIS CANADA	Not a hazardous substance according to WHMIS 2015
--------------	---

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 9/14/2020