



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666



Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier "ACÉTATE 3" BUFFER, PH 4.0		Product Use Laboratory use	
Chemical formula -		Product code TA-0022	Molar weight
Chemical name / Commercial name / Synonymous "ACETATE 3" BUFFER (PH4.0)			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666		CENTRE ANTI-POISON DU QUÉBEC 800-463-5060
Date SDS 12/2/2019	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	Serious eye damage/eye irritation - Serious eye damage category 1 Liquides inflammables category 4 Skin corrosion/irritation - Skin corrosion category 1
Signal Word	DANGER
Hazards statements (H)	H227 Combustible liquid. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.
Precautionary statements (P)	P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking. P260 Do not breathe dust / fume / gas / mist / vapours / spray. P264 Wash the areas of the body that have been in contact with the product after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P321 Specific treatment (see section 4 of the SDS and on this label). P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use water spray or alcohol-resistant foam, or dry powder or carbon dioxide for extinction. P403 Store in a well-ventilated place. P405 Store locked up. P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.
PICTOGRAMS	
Other dangers	NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)
	Health 1 Fire 0 Reactivity 0 Special danger

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Acide acétique	64-19-7	38
Acétate de sodium	6131-90-4	19
Eau	7732-18-5	Balance

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. If irritation persists, seek medical attention.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	If the person is conscious, give water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	No longer flammable at this concentration. But remains combustible.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Data not available.
Hazardous combustion / decomposition products	Hazardous decomposition products formed under fire conditions. Carbon oxides. - Sodium oxides.
Special fire and explosion hazards	May react violently with incompatible products (Ref Section 10).
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personnal precautions, protective equipment	Evacuate personnel to safe areas. Cut off all sources of ignition. Absorb the product with sand or vermiculite. Dilute residues with water, clean and rinse. Ensure a good ventilation of the premises. Dispose of residues in a container for disposal of hazardous materials. When handling, wear suitable safety equipment. Use breathing apparatus if necessary. Avoid breathing vapours, mist or gas.
--	--

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Store in a cool, dry place. Store in a well-ventilated area. Keep container tightly closed and store away from heat, water, moisture, and incompatible products. Keep away from sources of ignition - No smoking. Take measures to prevent the accumulation of electrostatic charges. Protect from the sun's rays.
Methods of handling	Keep away from sources of ignition - No smoking. Avoid inhalation of vapour or mist. Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14)

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Acetic acid	64-19-7	TWA	10.000000 ppm 25.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	15.000000 ppm 37.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	10.000000 ppm	Canada. British Columbia OEL
		STEL	15.000000 ppm	Canada. British Columbia OEL
		TWAEV	10.000000 ppm 25.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	15.000000 ppm 37.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10 ppm 25 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	15 ppm 37 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	10 ppm	Canada. British Columbia OEL
		STEL	15 ppm	Canada. British Columbia OEL
		TWAEV	10 ppm 25 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	15 ppm 37 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	10.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)
Components	CAS-No.	Control	Value	Basis
SODIUM ACETATE (TRIHYDRATE)	6131-90-4	TLV, TWA, STEL	No data available	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TLV, TWA, STEL	No data available	Canada. British Columbia OEL
		TLV, TWA, STEL	No data available	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

Data source	Sigma-Aldrich (Millipore Sigma)
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	incolore-
Odour	Odeur forte et irritante.
Odour threshold	Data not available
pH	4.
Melting point / Freezing point	Data not available
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Solubility	Soluble dans l'eau..
Vapour density	Data not available
Relative density	1.093g/ml
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Stable under normal conditions.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Heat, flames, sparks. Avoid contact with incompatible materials and extreme temperatures.
Incompatible material	When pure, the products react with the following products: Strong oxidizing agents (chromic acid, nitric acid, peroxides, chlorates and perchlorates), bases, alcohols, carbonates, hydroxides, oxides, phosphates, 5-azidotetrazole, bromine pentafluoride, chromium trioxide, hydrogen peroxide, potassium permanganate, sodium peroxide, phosphorus trichloride, heat and moisture. Reacts violently in contact with fluorine and potassium nitrate.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. Carbon oxides. - Sodium oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

ACETIC ACID, GLACIAL

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe burns and destruction of ocular tissue that can lead to corneal ulceration and blindness.
- Skin	Severe burns and tissue ulcerations. May be fatal, if the extent of the burns is considerable.
- Inhalation	Spasms, irritation and inflammation of the nose, throat and lungs. Edema of the larynx and bronchi. Chemical pneumonitis and pulmonary edema that can lead to death.
Acute toxicity (Ingestion)	Corrosion and ulceration of the mouth, throat, esophagus, stomach and abdominal wall. Dysphagia, kidney damage, bloody diarrhea and vomiting, diaphoresis, intense thirst, shock, circulatory collapse, unconsciousness, coma and can lead to death.
Chronic exposure effects / symptoms	Burning sensation, conjunctivitis, hyperkeratosis, nervous disorders, chest pain, dental erosion, cough, dyspnea, laryngitis, headache, dizziness, diarrhea, asthenia, irritability, weight loss and loss of appetite, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 3,530 mg/kg. LD50 Dermal - Rabbit - 1060 mg/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat -4h - 11.4 mg/L (4400 ppm - 4 h) LC50 Inhalation - Mouse- 1hre - 5620 ppm

SODIUM ACETATE (TRIHYDRATE)

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Irritation and tearing.
- Skin	Irritation.
- Inhalation	Irritation of the mucous membranes and respiratory tract. Nervous disorders, dizziness, cough, dyspnea, headache, nausea and vomiting.
Acute toxicity (Ingestion)	Irritation of the mucous membranes. Nervous disorders, gastrointestinal disorders, cramps, enteritis, diarrhea, headache, dizziness, convulsions, nausea and vomiting.
Chronic exposure effects / symptoms	Sensation de brûlure, troubles nerveux, vertiges, maux de tête, toux, dyspnée, laryngite, perte d'appétit, nausées et vomissements.
DL50 (specify species and route of entry)	Data based on the anhydrous product: LD50 Oral - Rat - 3530 mg/kg. LD50 Dermal - Rabbit - >10 g/kg
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 1 h - > 30,000 mg/m3. Data based on the anhydrous product:

SUMMARY

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	To our knowledge, the product has not been fully evaluated
Inhalation	To our knowledge, the product has not been fully evaluated
Skin	To our knowledge, the product has not been fully evaluated
Eyes	To our knowledge, the product has not been fully evaluated
Chronic exposure effects / Symptoms:	To our knowledge, the product has not been fully evaluated
ETA Mix (Estimated Acute Toxicity)	LD50 Oral: 5887mg/kg - Rat LD50 Dermal: 2251 mg/kg - Rabbit LC50 Inhalation: 24 mg/L - 4h - Rat

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Acetic acid. Toxicity to fish: Semi-static test LC50 - Oncorhynchus mykiss: > 1,000 mg/l - 96 h Toxicity to daphnia and other aquatic invertebrates: EC50 - Daphnia magna: > 300.82 mg/l - 48 h Sodium acetate: LC50 - Lepomis macrochirus - 5000 mg/l - 24 h - static EC50 - Daphnia magna (Water flea) - > 1000 mg/L - 48h. CE50 Pseudomonas putida - 7200 mg/l - 18h
Persistence and degradability	Biodegradability Result: - Readily biodegradable Soluble in water. Persistence is unlikely based on the information provided.
Bioaccumulative potential	Data not available.
Mobility in soil	Probable mobility in the environment due to its solubility in water.
Other adverse effects	Data not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Comply with federal, state and local regulations regarding waste disposal.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	3265
UN Proper shipping name	LIQUIDE ORGANIQUE CORROSIF, ACIDE, N.S.A. (Acide acétique)
Transport hazard class(es)	8 Corrosive substances
Packing group	III
Limited quantity index	5L
ERAP Index	-
Special precautions	16

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Serious eye damage/eye irritation - Serious eye damage category 1 Liquides inflammables category 4 Skin corrosion/irritation - Skin corrosion category 1
--------------	--

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 12/2/2019