



Centre Anti-Poison pour le Québec: (800) 463-5060

Tél. (Qc): (418) 660-8666 / 800-890-8666



Fax. (Qc): (418) 660-8998

SAFETY DATA SHEET

SECTION 01 - PRODUCT AND COMPANY IDENTIFICATION

Product Identifier OXALIC REAGENT (TINT ETCH)		Product Use Laboratory use	
Chemical formula -		Product code TS-2020	Molar weight 20,01
Chemical name / Commercial name / Synonymous TINT ETCH, RÉACTIF OXALIQUE, OXALIC REAGENT			
Supplier's name Laboratoire MAT		Address-Street 610, Adanac Street	
City Québec		Province Québec	
Postal code G1C 7B7	Internet www.labmat.com	Phone number 418-660-8666 / 800-890-8666	
Emergency phone	CANUTEC: 613-996-6666		CENTRE ANTI-POISON DU QUÉBEC 800-463-5060
Date SDS 9/13/2018	SDS Prepared by Laboratoire MAT	E-Mail labmat@labmat.com	

SECTION 02 - HAZARDS IDENTIFICATION

Classification WHIMS / GHS	<p>Skin corrosion/irritation - Skin corrosion category 1A</p> <p>Serious eye damage/eye irritation - Serious eye damage category 1</p> <p>Acute toxicity - Oral category 2</p> <p>Acute toxicity - Dermal category 1</p> <p>Acute toxicity - Inhalation category 3</p>
Signal Word	<p>DANGER</p>
Hazards statements (H)	<p>H300 Fatal if swallowed.</p> <p>H310 Fatal in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H318 Causes serious eye damage.</p> <p>H331 Toxic if inhaled.</p>
Precautionary statements (P)	<p>P260 Do not breathe dust / fume / gas / mist / vapours / spray.</p> <p>P262 Do not get in eyes, on skin, or on clothing.</p> <p>P264 Wash the areas of the body that have been in contact with the product after handling.</p> <p>P270 Do no eat, drink or smoke when using this product.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.</p> <p>P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.</p> <p>P302 + P352 IF ON SKIN: Wash with plenty of soap and water.</p> <p>P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</p> <p>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER or doctor/physician.</p> <p>P321 Specific treatment (see section 4 of the SDS and on this label).</p> <p>P330 Rinse mouth.</p> <p>P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.</p> <p>P363 Wash contaminated clothing before reuse.</p> <p>P403 + P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with local / regional / national / international regulations or contact a specialist waste disposal company.</p> <p>P261 Avoid breathing dust / fume / gas / mist / vapours / spray.</p> <p>P311 Call a POISON CENTER or doctor/physician.</p>
PICTOGRAMS	
Other dangers	<p>NFPA (Risk: 0=No risk; 1=Slight; 2=Moderate; 3=Signifiant; 4=Extreme)</p>
	<p>Health 4</p> <p>Fire 0</p> <p>Reactivity 0</p> <p>Special danger</p>

SECTION 03 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingrédients (Dénomination chimique / synonymes)	Numéro CAS et tout identificateur unique	Concentration (%)
Acide hydrofluorique	7664-39-3	12
Acide oxalique dihydrate	6153-56-6	14
Eau	7732-18-5	Balance

SECTION 04 - FIRST AID MEASURES

Eye contact	Wash eyes with large amounts of water for at least 15 minutes while holding eyelids apart to rinse eyes. If irritation persists, seek medical attention.
Skin contact	Treat the exposed skin with a 2.5% calcium gluconate gel, repeated application, until the burning sensation ceases. Wash skin with plenty of water for at least 15 minutes. Remove soiled clothing. Consult a physician.
Inhalation	Move the unwell person to the fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	Get immediate medical help. While awaiting the arrival of the aid, the patient may be ingested with a solution of 10% calcium gluconate or 5% calcium chloride. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
Most important symptoms and effects (acute and delayed)	Ref. section 11.
Immediate medical attention and special treatment, if necessary	In case of medical consultation, keep this sheet available.
General advice	Show this safety data sheet to the doctor in attendance.

SECTION 05 - FIREFIGHTING MEASURES

Flammability	No
Ignition conditions	Not flammable or combustible.
Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Not applicable.
Dangerous fumes - combustion	When heated to decomposition, the product emits toxic fumes: Carbon oxides. Hydrogen fluoride gas.
Hazardous combustion / decomposition products	Hazardous decomposition products formed under fire conditions. - Gaseous hydrogen fluoride.
Special fire and explosion hazards	May react violently with incompatible products (Ref Section 10). The contact of hydrofluoric acid with certain metals can release hydrogen, a highly flammable gas. Violent and explosive reactions may occur in contact with: chlorosulfonic acid, nitric acid + glycerin, nitric acid + lactic acid, nitric acid + propylene glycol, sulfuric acid, acetic anhydride, ammonium hydroxide, arsenic trioxide, calcium oxide, ethylene diamine, fluorine, mercuric oxide + organic materials, oleum, phosphorus pentoxide potassium, potassium hydroxide, potassium permanganate, propylene oxide, sodium, sodium hydroxide and vinyl acetate. Hydrofluoric acid reacts violently with glass. Oxalic acid dihydrate in high concentration in the air is capable of creating a dust explosion. Reacts with certain silver compounds to form silver oxalate which is explosive.
Special protective equipment and precautions for firefighters	Discard incompatible substances if this can be done without risk. Firefighters should be equipped with standard protective equipment, fireproof clothing, face mask, gloves, protective boots and, where appropriate, self-contained breathing apparatus.

SECTION 06 - ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up / Personal precautions, protective equipment	Evacuate personnel to safe areas. If it is hydrofluoric acid in solution, it may be neutralized with sodium carbonate or calcium carbonate in a mixture, optionally, depending on the quantities, with an inert material. Use a respirator as needed. Ensure adequate ventilation. When handling, wear appropriate safety equipment. Prevent further leakage or spillage if it is safe to do so. Discharge into the environment must be avoided.
---	--

SECTION 07 - HANDLING AND STORAGE

Conditions for safe storage	Do not store in glass. Store in corrosive resistant polyethylene container with a resistant inner liner. Keep container tightly closed in a dry and well-ventilated place. Store in cool place. Protect from the sun's rays. Keep container tightly closed and store away from heat, water, moisture, and incompatible products.
Methods of handling	Wear personal protective equipment when handling. Always ensure good ventilation. Transport according to TDG (ref Section 14). Always open containers slowly to allow any excess pressure to vent. Avoid inhalation of vapour or mist. Provide an emergency kit nearby.

SECTION 08 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
Hydrofluoric acid	7664-39-3	(c)	2.000000 ppm 1.600000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks				
		C	2.000000 ppm	Canada. British Columbia OEL
		TWAEV	0.500000 ppm	Canada. Ontario OELs
		CEV	2.000000 ppm	Canada. Ontario OELs
		C	3.000000 ppm 2.600000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
A substance which may not be recirculated in accordance with section 108				
		TWA	0.500000 ppm 0.400000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	0.5 ppm 0.4 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		(c)	2 ppm 1.6 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		C	2 ppm	Canada. British Columbia OEL
		C	3 ppm 2.6 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
A substance which may not be recirculated in accordance with section 108				
		TWA	0.500000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		C	2.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	0.5 ppm	USA. ACGIH Threshold Limit Values (TLV)
		C	2 ppm	USA. ACGIH Threshold Limit Values (TLV)
Components	No.-CAS	Value	Control parameters	Basis
Oxalic acid	144-62-7	TWA	1.000000 mg/m ³	Canada. LEP Colombie Britannique
		STEL	2.000000 mg/m ³	Canada. LEP Colombie Britannique
		TWA	1.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarques	La limite d'exposition professionnelle est basée sur les effets de l'irritation et son ajustement pour compenser les emplois du temps de travail inhabituels n'est pas nécessaire			
		STEL	2.000000 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
La limite d'exposition professionnelle est basée sur les effets de l'irritation et son ajustement pour compenser les emplois du temps de travail inhabituels n'est pas nécessaire				
		TWAEV	1.000000 mg/m ³	Canada. Ontario OELs
		STEV	2.000000 mg/m ³	Canada. Ontario OELs
		VEMP	1.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		VEMP	1 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		VECD	2 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		VECD	2.000000 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	1 mg/m ³	Canada. British Columbia OEL

		STEL	2 mg/m ³	Canada. British Columbia OEL
--	--	------	---------------------	------------------------------

Data source	Sigma-Aldrich.
Ventilation	Fan.
Respiratory	If the permissible levels are exceeded, use a mechanical filter / cartridge against NIOSH vapors or a respirator with air supply.
Gloves	Handle with gloves.
Eyes	Safety goggles with safety shutters.
Shoes	Safety shoes.
Clothing	Labcoat. Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Engineering control	Have safety showers and eyewash stations in the workplace in case of an emergency and a ventilation system to maintain the level of concentrations in the air below the exposure limit values.

SECTION 09 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.
Appearance	Liquide incolore avec présence d'un dépôt blanc-
Odour	Donnée non disponible.
Odour threshold	Data not available
pH	<1.
Melting point / Freezing point	Data not available
Initial boiling point	Data not available
Boiling range	Data not available
Flash point	Data not available
Evaporation rate	Data not available
Flammability	No
Lower flammable / Explosive limit	Data not available
Upper flammable / Explosive limit	Data not available
Vapour pressure	Data not available
Solubility	Miscible dans l'eau.
Vapour density	Data not available
Relative density	1.19 (Théorique)g/ml
Partition coefficient water/n-octanol	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	Data not available

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	Non-reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Stable under normal conditions.
Conditions of instability (Including sensitivity to shock / static discharge / vibration)	Excessive heat and contaminations of all kinds. Light sensitive.
Incompatible material	Strong bases, concrete, carbonates, cyanides, silicone-based materials, oxidizing or reducing materials, alkali metals, organic and combustible substances, sulphides, glass, heat, moisture, sun rays and light. Strong oxidizing agents (nitric acid, perchloric acid, peroxides, chlorates and perchlorates), acid chlorides, corroded steel, furfuryl alcohol, silver and its salts, bases, alkali metals, chlorate and sodium hypochlorite, heat and humidity.
Hazardous decomposition products	Hazardous decomposition products formed under fire conditions. - Gaseous hydrogen fluoride. Carbon oxides.

HYDROFLUORIC ACID (70%)

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	(The liquid as well as the vapors are extremely corrosive). Severe burns and destruction of ocular tissue that can lead to corneal ulceration and blindness.
- Skin	(The liquid as well as the vapors are extremely corrosive). Severe burns and tissue ulcerations. Burns can penetrate deeply into the underlying tissues of the skin to reach the bone, and attack the bone through secondary hypocalcemia. May be fatal, if the extent of the burns is considerable.
- Inhalation	Spasms, irritation and inflammation of the nose, throat and lungs. Edema of the larynx and bronchi. Chemical pneumonitis and pulmonary edema that can lead to death.
Acute toxicity (Ingestion)	Corrosion and ulcerations of the gastrointestinal tract. Dysphagia, liver and kidney damage, abdominal pain, cramps, diarrhea, melena, hematemesis, necrosis of the esophagus and stomach, stenosis, cardiac disorders, hypocalcemia, convulsions, circulatory collapse, unconsciousness, coma, and death.
Chronic exposure effects / symptoms	Burning sensation, nerve disorders, lung damage, chest pain, cough, dyspnea, bronchitis, headache, dizziness, sweating, salivation, tremors, dental enamel abrasion, anemia, leukopenia, fatigue, weight loss and loss of appetite, convulsions, nausea and vomiting. Prolonged exposure to this product may promote the development of skin ulcers, bone (osteosclerosis) and joint lesions, fluorosis, secondary hypocalcemia, and may even result in gangrene.
DL50 (specify species and route of entry)	LD50 Oral - Data not available. LD50 Dermal - Data not available.
CL50 (specify species and route of entry)	LC50 Inhalation - Rat - 1h - 1 307-2 340 ppm

OXALIC ACID, DIHYDRATE

Routes of exposure	Ingestion, inhalation, skin and eyes.
Acute exposition effects / symptoms:	By exposure route below.
- Eyes	Severe irritation and burns that may cause permanent eye damage.
- Skin	Severe irritation and tissue burn. Prolonged contact with oxalic acid solutions produces skin lesions that become worse over time; these can cause gangrenous cyanosis.
- Inhalation	Spasms, irritation and inflammation of the nose, throat and lungs. Edema of the larynx and bronchi. Chemical pneumonitis and pulmonary edema that can lead to death.
Acute toxicity (Ingestion)	Burns and corrosion of the digestive tract. Possibility of oesophageal or gastric perforation and bleeding, kidney damage, abdominal pain, diarrhea, nausea and vomiting, hypocalcemia, paresthesia, myoclonus, spasmodic muscle contractions, fast and irregular pulse, convulsions, hypotension, coma and can lead to death.
Chronic exposure effects / symptoms	Burning sensation, dermatitis, conjunctivitis, skin lesions, brittle and blackish nails, kidney damage, nerve disorders, chest pain, cough, dyspnea, laryngitis, headache, dizziness, albuminuria, irritability, sweating, salivation, fatigue, loss of weight and loss of appetite, seizures, nausea and vomiting.
DL50 (specify species and route of entry)	LD50 Oral - Rat - 375 mg/kg. LD50 Dermal - Rabbit - 20 000 mg/kg
CL50 (specify species and route of entry)	Data not available.

SUMMARY

Acute exposure effects / Symptoms:	By exposure routes below.
Ingestion	To our knowledge, the product has not been fully evaluated
Inhalation	To our knowledge, the product has not been fully evaluated
Skin	To our knowledge, the product has not been fully evaluated
Eyes	To our knowledge, the product has not been fully evaluated
Chronic exposure effects / Symptoms:	To our knowledge, the product has not been fully evaluated
ETA Mix (Estimated Acute Toxicity)	LD50: 48 mg/kg -Oral (Undefined specie) LD50: 8 mg/kg -Dermal (Undefined specie) LC50: Data not available

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity	Data not available.
Persistence and degradability	Data not available.
Bioaccumulative potential	Data not available.
Mobility in soil	Data not available.
Other adverse effects	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Method	Dispose of contents / container in accordance with local / regional / national / international regulations / or contact a specialist waste disposal company.
Contaminated Packaging	Dispose of as unused product.

SECTION 14 - TRANSPORT INFORMATION

UN Number	2922
UN Proper shipping name	LIQUIDE CORROSIF, TOXIQUE, N.S.A. (acide fluorhydrique)
Transport hazard class(es)	8 Corrosive substances 6.1 Toxic substances
Packing group	I
Limited quantity index	0L
ERAP Index	3000
Special precautions	16

SECTION 15 - REGULATORY INFORMATION

WHIMS CANADA	Skin corrosion/irritation - Skin corrosion category 1A Serious eye damage/eye irritation - Serious eye damage category 1 Acute toxicity - Oral category 2 Acute toxicity - Dermal category 1 Acute toxicity - Inhalation category 3
---------------------	---

SECTION 16 - OTHER INFORMATION

Further information

The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. It does not represent any guarantee of the properties of the product. Laboratoire MAT Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Last Update: 9/13/2018